

MAVOWATT 30

The Troubleshooter



- Detection of mains interference before it's too late
- Mains quality testing per EN 50160,
 EN 61000-4-7 and EN 61000-4-15
- Continuous overview of energy costs
- Simple handling and automatic detection of electrical system types
- Automatic analysis/evaluation of measurement results
- Reports are generated by simply pressing a key with ultramodern DranView 6 Power Quality software

Special Offers

on Back

Put an end to unscheduled downtime and exorbitant repair costs due to mains interference!

Let the expert analyze your systems! MAVOWATT 30

Keep a close eye on your electrical systems with the MAVOWATT 30 from GOSSEN METRAWATT. The MAVOWATT 30 detects all relevant mains interference such as flicker, transients, voltage dips and voltage failures. Innovative analysis algorithms transform the MAVOWATT 30 into a universal instrument that provides the user with active troubleshooting assistance.

The basic instrument:







* Prices do not include legally applicable VAT

Technical data:

- 8 measurement inputs, 4 for voltage (differential), 4 for current (current transformer), for measurement with line frequencies of 50, 60 and 16²/₃Hz
- Storage of data to compact flash card Memory card with up to 32 GB
- Power supply:
 - → Via the charger: 90 to 264 V / 47 to 63 Hz
 - → Installed rechargeable battery for up to 3 hours

Scope of delivery:

- Power disturbance analyzer
- Set of measurement cables
- Rechargeable battery and charger
- 4 GB compact flash card
- Factory calibration certificate
- DranView 6 Pro software
- Condensed operating instructions
- Carrying pouch

Accessories – flexible current clamps:

- Our flexible current clamps are matched for use with the MAVO-WATT 30, 40 and 70, as well as any other measuring instruments with 1.5 VAC measurement inputs and Hypertronics plug.
- The sensors are capable of enclosing one or more conductors of various types (insulated cables, conductor bars, pipes) without interrupting the primary circuit.
- Internal batteries allow for autonomous operation of the measuring amplifier (battery service life of up to 1500 working hours).
- METRAFLEX 3001/3003XL Measuring range: 30/300/3000 A
- DRANFLEX 300MH Measuring range: 3/30/300 A
- External supply power is provided by a DC/DC converter ISOFLEX-MHXL (optionally available)

MAVO WATT 30	Article no.	M817A
METRAFLEX 3001XL	Article no.	Z207H
METRAFLEX 3003XL	Article no.	Z207
DRANFLEX 300MH	Article no.	Z207N



GMC Instruments Belgium NV/SA

Galgenbergstraat, 52 • 9290 Berlare • Belgium Phone: +32 52 399 750 • Fax: +32 52 399 760

www.gmc-instruments.be • info@gmc-instruments.be